

# tretford®

SPECIFICATIONS	TRETTFORD ROLL & RUG	TRETTFORD INTERLIFE TILE & PLANK
<b>CONSTRUCTION:</b> Carded fibres formed into a continuous corrugation.	Bonded with Phthalate Free PVC to a Hessian backing	Bonded with Phthalate Free PVC to a post consumer recycled PET backing
<b>MATERIALS &amp; COMPOSITION:</b>	80% Goat Hair, 15% Nylon, 5% Viscose	70% Goat Hair, 30% Nylon
<b>COLOUR DYES:</b>	512 Dapple Grey, 538 Silver Birch and 587 Double Cream are manufactured using undyed goat hair. All other colours are dyed without bleaching.	
<b>WARRANTIES:</b>	Wear guarantee: BS EN 1307:2005 Class 33 LC2 heavy commercial use. Lifetime anti-ravel / non-zipper guarantee.	
<b>DIMENSIONS &amp; WEIGHT:</b> Length / Packing: Thickness: Weight:	2m wide Roll lengths will vary 7mm ca. 2.75kg/m <sup>2</sup>	50 x 50cm tile, 100 x 25cm plank Tile: 5sqm per box   Plank: 3sqm per box 8mm ca. 3.7kg/m <sup>2</sup>
<b>FLAMMABILITY:</b>	BS 4790:1987 Mean burning radius: 25mm, Class: low BS EN ISO 11925:2002, BS EN ISO 9239 - 1: Euroclass Cfl-s1 (B1)	
<b>THERMAL INSULATION:</b> Thermal resistance:	Conclusion: Suitable for all commercial / contract installations including institutional, commercial and public buildings. (BS 4745:1971 / ISO 8302:1991)	
<b>ELECTRICAL PROPERTIES / STATIC:</b>	Test results confirm satisfactory thermal properties for underfloor heating. ISO 6356:2000 BS EN - 1.3kV BS EN 14041:2004: Classified as anti-static.	
<b>DYNAMIC LOADING:</b>	(BS 4052:1987) Thickness loss % after 1000 impacts: 13.33%	
<b>DIMENSIONAL STABILITY:</b>	(BS EN 986:2005) Dimensional stability test requirements: -0.2% - +0.2%	
<b>COLOUR FASTNESS</b> To light:	N/A	
<b>IMPACT SOUND INSULATION:</b>	Passed	
<b>SOUND ABSORPTION:</b>	(BS 1006:1990) Colour change: 5-6, very slight to none.	
	(BS 2750:1980) (EN ISO 10140-1)	
	c. 23dB	c.24dB
	This carpet meets the requirements of the building regulations by a useful margin.	
	(EN ISO 354:2003) (EN ISO 11654:1997)	
	Noise reduction coefficient: 0.21 (250-2,000 Hz) Sound absorption grade: 0.25 (125-4,000 Hz)	
	130 255 515 1025 2025 4075 0.01 0.03 0.10 0.27 0.42 0.41	125 250 500 1000 2000 4000 0.02 0.05 0.14 0.29 0.27 0.35
<b>MOTHPROOFING:</b>	(BS 4797:1972) (SIS 650220) tretford is moth-resistant to European standards.	
<b>CASTOR CHAIR PROTECTORS:</b>	(For appearance retention purposes) Recommended with 3★ colours. Mandatory with 1★ and 2★ colours.	
<b>COUNTRY OF MANUFACTURE:</b>	Ireland Available in 48 classic colours	Germany Available in 35 classic colours
<b>INSTALLATION:</b>	tretford cord carpet is a natural fibre product. Different production runs of the same product may therefore be subject to shade variation. This is not a defect or a manufacturing fault.	
<b>SUSTAINABILITY:</b>	For installation guidelines, please refer to your tretford website in your country. Refers to rugs fully installed - no secondary backing.	
	     	